



## KEIM INNOSTAR®

---

KEIM Innostar is an innovative interior paint, with excellent coverage meaning that in the majority of cases only one coat is required, even onto new, unpainted plaster, without the need for undercoats or mist coats.

KEIM Innostar is environmentally friendly, quick and easy to use. KEIM Innostar is free from plasticisers, solvents and preservatives and is practically odour-free so rooms can be occupied quickly after application.

**KEIM Innostar – Interior one coat paint system.**

# KEIM INNOSTAR®

## TECHNICAL INFORMATION

### 1 Field of application

KEIM Innostar has excellent covering capacity in combination with an outstandingly elegant white colour shade. It is suitable for all interior wall and ceiling surfaces.

KEIM Innostar can be used for new, unpainted or previously painted surfaces and is ideal for large areas. KEIM Innostar has outstanding opacity so that one coat application is almost always sufficient.

### 2 Product properties

- Ultra-covering
- High degree of whiteness
- Very low-odour
- Highly permeable
- Ecologically sound
- Matt surface
- Solvent and plasticiser-free
- Incombustible - A2-s1, d0
- Nature-plus certification
- Disinfectant resistance
- Cradle to Cradle Certified®

**KEIM Innostar**  $s_d \leq 0.01\text{m}$

**Colour Shades:** White, KEIM Palette Exclusive and Avantgarde swatch.

### 3 Application instructions

#### Substrate preparation

All loose, flaking and unstable material must be identified and then thoroughly removed, all surfaces must be thoroughly washed down with clean cold water to remove all surface dirt and dust. When all surfaces are clean, sound, wind dry, dust free and free from all surface contaminants, decoration using KEIM Innostar may proceed.

### Application

KEIM Innostar should be applied as a single coat by brush, roller or airless spray.

### Consumption

Approx. 0.125lt/m<sup>2</sup>

Consumption rates are offered for guideline purposes only and are quoted for smooth surfaces. Actual rates are the responsibility of the applicator. Project specifications should be referred to for specific rates.

### Cleaning of tools

Clean immediately after use with water.

### 4 Packaging

5 lt & 12.5 lt containers

